

Estop C² Stain Clean

Oil and Stain Remover for Concrete

Description

Estop C² Stain Clean is the most effective poultice cleaner for removing the toughest oil and grease stains from concrete, pavers stone and other porous surfaces.

When **Estop C² Stain Clean** is poured on the embedded stain, it penetrated into the porous surface making an immediate poultice. It pulls the contaminants out of the substrates.

Uses

Estop C² Stain Clean is suitable for removing stains from:

- Concrete
- Blocks
- Pavers
- Brick
- Tiles

Advantages

- Effective on old, deeply embedded stains.
- Easy to use, just pour on the surface. No need for scrubbing or mixing.
- Practical, will not leave residue.
- Universal, works on concrete, blocks, pavers, brick and tiles.
- Comprehensive, removes brake and power steering fluids, motor oil, hydraulic fluids, anti-freeze, cooking oils, food grease, and other oil and grease stains.
- Unique, it will not discolor the concrete.
- Safe on granite, marble, travertine and limestone.
- Water based and non-toxic.

Physical Properties

| | |
|---------------------------|--|
| Form | Viscous, white liquid slight citrus odor |
| Specific Gravity | 0.80 |
| pH | 10.5 |
| WT/GAL | 6.66 lbs |
| Flash Point ASTM D3278 | >200°C (93°F) |
| Freeze Point | 0°C (32°F) |
| VOC Content | 4% maximum |

Application Instruction

Surface Preparation

Do not pre-wet.

Scrape and remove any buildup or debris from the surface.

Application

Shake well and pour onto the stained surface until the stain is completely covered. The batter thick poultice will automatically reach its required thickness as it spread out across the stain surface.

Let the poultice dry for 12 - 24 hours or overnight.

Protect from foot traffic, rain and direct sun exposer during well period using plastic tent. Avoid using tightly adhered plastic cover.

The poultice surface will develop cracks as it contracts and dries. A fully developed network of cracks indicates the poultice is completely dry.

Drying time may vary with weather conditions, temperature, wind and humidity.

Most oil and grease stains can be cleaned with one application. Severe, deeply embedded stains may redevelop after cleaning, requiring further applications.

Estop C² Stain Clean can be applied using solvent-resistance brushes, roller, or a trowel to apply on horizontal or vertical surfaces.

****DO NOT DILUTE OR ALTER Estop C² Stain Clean**

Cleaning

Estop C² Stain Clean can be clean up using a scrapper or other stiff-bristled brush, and dustpan to sweep up dried poultice and dispose. High pressure air can be used to blow out extremely porous surfaces after sweeping.

Packing Size

| | |
|--|------------------|
| Estop C² Stain Clean | 3.5L or 20L pail |
|--|------------------|

Coverage

| Estop C² Stain Clean | Coverage |
|--|----------------------------|
| 1.0L | Approx. 0.5m ² |
| 3.5L | Approx. 1.75m ² |

Noted: The coverage will depend on concrete quality, porosity, job site conditions, temperature and relative humidity.

Technical Support

Estop offers a technical support package to specifiers, end-user and contractors, as well as on site technical assistance.

Storage

Estop C² Stain Clean material should be stored at maintain temperature 4-38°C and should be protect from extreme temperature and keep from freezing.

Do not double-stack pallets.

Do not alter or mix with other chemicals.

Do not reused container or remove labels and keep this material out of the reach of children.

Estop C² Stain Clean has a shelf life of 2 years in unopened factory sealed container.

Precautions

Do not take internally. It may irritate eyes and skin. Protective clothing and gloves are recommended to prevent sensitization to these materials. In case of eye contact, flush with soap and clean water, and seek medical attention immediately. Keep out of reach of children.

Additional Information

Estop manufactures and offer a wide range of complementary products which includes waterstops, waterproofing products, grouts, anchors, specialized flooring products. In addition, a wide range of products formulated for repair and refurbishment of spalled concrete are available.

Important Note

Estop products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which may be obtained on request. Whilst Estop endeavors to ensure that any advice, recommendation, specification or information in may give is accurate and correct, it shall not, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.