

Estofom OB

High Efficient Mould Releasing Agent

Description

Estofom OB is specially blended with high efficient releasing properties. It is oil based and supplied in a pale straw coloured liquid. **Estofom OB** shall be used as supplied without adding in with any water or solvent.

Uses

It is specially design to provide quick, clean and easy stripping of moulds and formworks.

Advantages

- Ensure stain-free concrete
- Oil based inhibits corrosion of steel formworks
- Can be used on all types of formworks
- Minimizes cleaning moulds or formworks

Physical Properties

Specific Gravity at 25°C	0.9
Colour	Pale straw
Service Temperature	70°C max

Application Instructions

Preparation of new moulds

No surface preparation is required.

Preparation of used moulds

All adherent materials must be removed prior to use. The moulds or formworks shall be clean before application of **Estofom OB**.

Mixing

No mixing is required.

Application

Use brush, sponge or conventional mould oil sprayer to apply **Estofom OB**. The correct nozzle size should be ensured, if a sprayer is used. Ponding or accumulation of excess mould oil should be avoided. It should be applied in a continuous even film.

If there is a delay period for more than 48 hours, the surface should be recoated. Non-absorbent surfaces shall be applied in a single layer only.

Cleaning

The spillages of **Estofom OB** should be absorbed into sand, earth or vermiculite and transfer to suitable container.

Packing & Size

Estofom OB	210 litre drum 20 litre pail
-------------------	---------------------------------

Coverage

Estofom OB	20 to 60 m ² /litre, depend on type and porosity of steel mould used
-------------------	---------------------------------------------------------------------------------

Technical Support

Estop offers a comprehensive range of high performance, high quality of repair product for both new and existing concrete surfaces. In addition, the company offers a technical support package to specifies, end-users and contractors, as well as on-site technical assistance.

Storage

Estofom OB should be stored on pallets under dry conditions in original un-open drum. Under these conditions the product will have a shelf life of 12 months.

If stored in extreme heat locations the shelf life may be reduced

Fire

Estofom OB is flammable. Adequate ventilation should be ensure when use. Do not use near naked fire or smoke during use.

Precaution

Estofom OB should not be swallowed and avoid to be in contact with skin or eyes. Wear gloves and goggles for protection. If swallowed, seek medical attention immediately

Do not induce vomiting.

Additional Information

Estop manufactures and offers a wide range of complementary products which includes waterstops, waterproofing products, grouts, anchors, specialized flooring products. In addition, a wide range of products formulated for repair and refurbishment of spalled concrete are available.